

Ingenico 5310

Countertop Range

A true hand-over terminal, ideal for PIN entry

- Ingenico 5310 is an excellent countertop solution for retailers, restaurants and service providers that offer credit and PIN based transactions.
- It has a small footprint that optimizes counter space. Its curly cable allows the merchant to easily and safely hand the terminal to the consumer for card swipe and PIN entry.
- The i5310 was designed for fast transaction acceptance with a 15 lines per second thermal printer, 32-bit processor, IP-capable high-speed modem and Ethernet communications. A simple keypad and large bright backlit display with 3 screen addressable keys make it very easy to use.



EMV
Fast transaction time



UNICAPT
Application compatibility



**Visa Approved
PED**



**TCP/IP
Ethernet**





Ingenico 5310

Built for fast transaction authorization

- V34 (33,600 bytes per second) modem provides fast transaction authorization and downloading.
- Long MSR swipe path increases operator first pass read success.
- Large backlit screen and keypad are easy to see in any lighting.
- 32 bit processor provides power for swift transaction completion.
- 15 lines per second printer and receipt pre-printing eliminate customer wait time.
- Ethernet and IP connectivity capability reduces transaction authorization time and cost.

Compact "all-in-one" terminal

- "All-in-one" design and integrated PIN pad eliminate counter clutter, "spaghetti cable" look and the need for a terminal swivel which can strain communication and power cables.
- Curly cable securely tethers base to terminal to optimize customer use while providing maximum security.
- Plug It modules: RS232, Ethernet, RS485... more to come.

Secure

- Visa approved PED, on-line/off-line terminal that eliminates tampering.
- DES and 3DES integrated PIN pad for secure online debit and EBT transactions.
- MasterSession and DUKPT key management.
- Secure local and remote software downloading.
- EMV 4.0 certified Level 1 and 2 smart card reader.



Backlit ergonomic style keyboard



Long MSR swipe path increases first pass read success



Terminal is handed to customer for PIN entry



"Easy load" 15 lines per second thermal printer

Memory	2 MB SRAM and 8 MB Flash
Processor	32 bit ARM processor
Security	Visa PED approved, DES or 3DES DUKPT or MasterSession management keys Secure local and remote software downloading Secure key downloading
Printer	15 lines per second thermal printer Easy load with end-of-paper roll detection Full graphics printing capability
Keypad	18 backlit keys including 3 screen addressable function keys
Display	LCD display, 128 x 64 pixels and graphics capability Backlit with adjustable contrast
Communication	V34 modem, transfers up to 33.6K bits per second (bps) Synchronous and asynchronous transmission TCP/IP Ethernet and TCP/IP
Magnetic card reader	Tracks 1, 2 & 3
Smart card reader	EMVco approved Level 1 reader UNICAPT 32 EMV Level 2 approved ISO 7816 1-2-3, Async/Sync. T=0 & T=1 Optional support for up to 3 Secure Access Modules (SAM) in SIM format
Connectivity	(2) RS232 ports and Ethernet support
Programming	UNICAPT secure multi-application platform and development environment Programmable in C
Environmental	Operating temperature: +5°C to +40°C (41F to 104F) Storage temperature: -20°C to +70°C (-2F to 158F)
Dimensions	Terminal: 20.9 x 9.6 x 6.0 cm (8.22 x 3.77 x 2.36 in.) Base: 20.2 x 9.1 x 4.0 cm (7.95 x 3.58 x 1.57 in.)
Weight	Terminal: 500 gr. (1.1 lb) Base: 910 gr. (2.0 lb)



Ingenico Inc.
1003 Mansell Road - Atlanta, GA 30076
Tel: (770) 594-6000 - Fax: (770) 594-6003
www.ingenico-us.com

Ingenico Canada Ltd.
79 Torbarrie Road - Toronto, Ontario - Canada M3L 1G5
Tel: (416) 245-6700 - Fax: (416) 245-6701
www.ingenico-ca.com

Groupe Ingenico 9, quai de Dion Bouton - 92816 Puteaux Cedex - France
Tel: 33 (0)1 46 25 82 00 - Fax: 33 (0)1 47 72 56 95 - www.ingenico.com

All rights reserved. This document is not binding and the specifications hereabove can be modified without prior consent.